

MEKI

QUIMI MOBILE TV



Model	24MQM8128	32MQM8128
LCD PANEL		
Module Level	New A + LCD	New A + LCD
Panel Size	23.8 inches	32 inches
Resolution Ratio	1920*1080	1920*1080
Viewing Angle	89/89/89/89 (Typ.) (CR≥10)	89/89/89/89 (Typ.) (CR≥10)
Display Area	527.04 (H) X 296.4 (V)mm	698.4 (H) X 392.85 (V)mm
Display Ratio	16:09	16:09
Screen Brightness	250cd/m2	350cd/m2
Backlight Type	E-LED	E-LED
MOTHERBOARD CONFIGURATION		
CPU	MTK 8788 4*Cortex-A73+ 4*Cortex-A53	MTK 8788 4*Cortex-A73+ 4*Cortex-A53
GPU	ARM Mali-G72 MP3 700MHz	ARM Mali-G72 MP3 700MHz
RAM	8GB	8GB
ROM	128GB	128GB
Android OS	Android 13	Android 13
WIFI	2.4G/5G dual-band WiFi	2.4G/5G dual-band WiFi
Bluetooth	BT4.2	BT4.2
Gyroscope	YES	YES
Wireless Screen Mirroring	YES	YES
MIC	YES	YES
Speaker	2*3W	2*6W
Port	USB *1; HDMI IN *1; Type_C*1	USB *1; HDMI IN *1; Type_C*1
Language Pattern	Multilingual	Multilingual
TOUCH SCREEN		
Touch Technology	Capacitive Technique	Capacitive Technique
Touch Scheme	Capacitor G+F+F	Capacitor G+F+F
Touch Count	10 Points Effective Touch	10 Points Effective Touch
Touch Medium	Finger or Capacitive Stylus	Finger or Capacitive Stylus
Touch Accuracy	≤2mm	≤2mm
Response Time	≤5ms	≤5ms
CAMERA		
Hardware Pixel	Build-in 4K 13 megapixel camera	Build- in 4K 8 megapixel camera
Field Angle	78°±5°	65°±5°
Dynamic Range	96db	96db
Focusing Mode	Auto Focus	Fixed-Focus
ELECTRICAL PERFORMANCE		
Input Voltage	AC110-220V	AC110-220V
Battery	10000mAh	10000mAh
Power Supply DC	12V/5A	19V/5A
Standby Power	≤1W	≤1W
Rated Power	≤30W	≤50W
Use Environment	Temperature -0 ° C to 60 ° C/Humidity 10%-90%RH	Temperature -0 ° C to 60 ° C/Humidity 10%-90%RH
Storage Environment	Temperature -5 ° C to 65 ° C/Humidity 10%-90%RH	Temperature -5 ° C to 65 ° C/Humidity 10%-90%RH
PRODUCT SPECIFICATIONS		
Shell Material	Plastic	Plastic
Base Size	Diameter 400MM, 5*Wheel	Diameter 400MM, 5*Wheel
Carton Size	695*500*245MM	825*495*195MM
Gross Weight	16.3KG	20.8KG