

MEKI

Digital "Z" Kiosk

- Landscape Layout

- Sturdy Stand

- Optional Android / Windows

- Easy Plug & Play



| Model No. | 32ZTP3576RK432 | 43ZTP3576RK432 | 49ZTP3576RK432 | 55ZTP3576RK432 | 65ZTP3576RK432 |
|------------------|--------------------|-----------------|------------------|------------------|------------------|
| Screen Size | 32" | 43" | 49" | 55" | 65" |
| Panel Type | a-Si TFT-LCD | | | | |
| Aspect Ratio | 16:9, Wide SXGA | | | | |
| Resolution | FULL HD 1920 x1080 | | | | |
| Viewing Angle | 178(H) / 178(V) | | | | |
| Brightness | 300cd/m2 | 300cd/m2 | 300cd/m2 | 350cd/m2 | 350cd/m2 |
| Active Area | 698.0 x 392.0mm | 944.5 x 531.0mm | 1077.3 x 605.9mm | 1209.8 x 680.4mm | 1427.4 x 802.2mm |
| Contrast | ≥1000:1 | | ≥3000:1 | | |
| Response Time | 8ms | 10ms | 10ms | 10ms | 8ms |
| Display Color | 8 bit | | | | |
| Service Lifetime | ≥50000 hours | | | | |
| Power | ≤50W | ≤90W | ≤110W | ≤130W | ≤180W |

| Touch System | |
|---------------------|---|
| Sensing Type | Infrared touch screen or capacitive touch screen (Multi 20points touch) |
| Response Time | 6ms |
| Connection | Full-speed USB (Driver free) |
| Light Transmittance | 88% Light Transmittance |
| Surface Protection | Anti-glare Tempered Glass with 3mm thickness Standard |

| Android Part* | |
|------------------|---|
| Operating System | Android 14.0 Version |
| Chipset | RK3576 |
| CPU | Quad-Core A72 + Quad-Core A53 CPU @ 2.2GHz |
| GPU | Mali-G52 |
| RAM | 4G / 8G |
| ROM | 32G / 128G |
| Internet | RJ45 |
| WIFI | Dual band WIFI6 |
| Bluetooth | BT5.4 |
| Interface | USB 3.0x1, USB 2.0x1, Type-C_OTG x 1, HDMI OUT x 1, 3.5mm earphones x 1, RJ45 x 1, DC x 1 |

*Optional OS (Operating system) to be Windows base (Charges to apply)

| Others | |
|-------------|--------------|
| Speaker | 2 x 5W |
| Key buttons | POWER |
| Software | Google Store |

| Power | |
|--------------|--------------|
| Power Supply | AC100 ~ 240V |
| Frequency | 50 / 60Hz |

| Working Environment | |
|-----------------------|--------------|
| Operation Temperature | 0°C ~ 50°C |
| Storage Temperature | -20°C ~ 60°C |
| Working Humidity | 85% |
| Storage Humidity | 85% |

| Packaging Information | | | | | |
|--------------------------------|---|---------------------|---------------------|---------------------|---------------------|
| Overall size of display screen | 736 x 432 x 60mm | 979 x 569 x 60mm | 1133 x 655 x 60mm | 1251 x 723 x 60mm | 1478 x 854 x 64mm |
| Package Dimensions (mm) | 855 x 165 x 575mm | 1090 x 165 x 715mm | 1238 x 168 x 800mm | 1380 x 168 x 865mm | 1635 x 160 x 1045mm |
| Base packaging size (mm) | 462 x 510 x 1,000mm | 528 x 498 x 1,090mm | 528 x 498 x 1,090mm | 528 x 498 x 1,090mm | 528 x 498 x 1090mm |
| Net weight (kg) | 19.7KG | 27.7KG | 32.5KG | 36.5KG | 45KG |
| Accessories | AC Power Cable, wheel, Remote controller, User Manual | | | | |